



Industrial 2 Port High Power PoE++ Media Converter (2 SFP)

IM-UM-0202-0002

Product Description

The Industrial 2 Port High Power PoE Media Converter with 2 SFP Ports offers robust and versatile network connectivity. It features 2x 10/100/1000BASE-T RJ45 ports with auto MDI/MDI-X functionality and 2 SFP ports supporting 100Base-FX or 1000Base-X dual mode with auto detection. Designed for high-power applications, it supports IEEE802.3af/at PoE+ (30W) and IEEE802.3bt PoE++ (90W).





Ports Interface

RJ45	2x RJ45 PoE ports w/ auto MDI / MDI-X
Optical	2x 1000Base-X or 100Base-FX dual mode SFP port w/ auto detection

Ethernet Standards

IEEE802.3
IEEE802.3u
IEEE802.3ab
IEEE802.3z
PoE 802.3af
PoE+ 802.3at
PoE++ 802.3bt

Indicators

PWR	Power status
PoE	PoE status
Ethernet	Link/Activity per port
SFP	Fiber link status

Environmental Standards

Rating	IP40
Storage Temperature	-40°C to 85°C
Operating Temperature	-40°C to 80°C
Humidity Tolerance	5% to 95%

Technical Specifications

Forward and Filtering Rate	14,880pps (10Mbps) / 148,800pps (100Mbps) / 1,488,000pps (1000Mbps)
Packet Buffer Memory	1 Mbit
Maximum Packet Length	9K bytes
Backplane Bandwidth	20Gbps
Address Table	2K MAC addresses
Processing Type	Store and forward

Power

Power Input	48-57VDC
Self Consumption	9W
Maximum Load Per Port	90W
Total PoE Budget	180W

Physical Properties

Weight	250g
Case Material	Aluminum
Dimensions (H x D x W)	95mm x 65mm x 30mm
Mounting	Optional DIN-Rail mount included Optional wall mount included

Any questions?

Visit our website at:
www.verdelon.com

Contact us: info@verdelon.com